

## LSPV Series

### LOAD SENSING PROPORTIONAL CONTROL VALVE



- LSPV 15
- Rated pressure: 350 bar (pump side)  
420 bar (actuator side)
- Rated Flow: 200 L/min

## Index

## Page No

• Features	02
• Section View	03
• Technical data	04
• Ordering code	05
• Hydraulic Diagram	08
• Inlet Section - Closed center	09
• Inlet Section - Open center	10
• Spool section assembly - hydraulic	11
• Spool section assembly - electro hydraulic	12
• Middle section - OBE (Super high performance E-H Control)	13
• Endlet section assembly (without additional P port)	14
• Endlet section assembly (with additional P port)	15
• Preferred spool flow	16
• Unit Dimensions	17
• Pressure Compensator type	18
• End elements option	18
• On-board electronics: OBE	19
• Technical data	20

## Features

### 1. System

#### Load pressure independent flow distribution

- Closed center, for load sensing variable pump system
- Open center, for fixed displacement pump system
- Priority function
- Various pilot control methods

### 2. Structure

- Sandwich plate of design
- Max. 9 middle section

### 3. Pressure

- Primary and secondary pressure relief valve
- LS relief valve: With LS pressure relief valve in each section

### 4. Flow

- Load pressure compensated
- Quick response
- Low hysteresis

### 5. Applications



Aerial work platform



Forestry machine



Drilling rigs



Mining truck



Concrete pump truck



Crane




Telehandler



Stone Crusher

### Section view



## Technical data

### General

Nominal Size			15
Structure	Stackable, proportional, load sensing, pre-compensated		
Type of connection	ISO BSP thread, metric thread (with SAE thread option per SAE J1626)		
Mass (kg)	Inlet element	Open center	9.8
		Closed center	6.5
	Middle section	Hydraulic operation	5.4
		Normal E-H operation	6.5
		Super E-H operation	7.5
End element			4.5

### Hydraulic

Nominal Size			15
Rated flow Q(L/min)	With load-holding function, without pressure compensator.	200	
	Without load-holding function, with pressure compensator.	190	
	With load-holding function, with pressure compensator.	160	
Max. operating pressure at port (bar)	P	350	
	LS	330	
	A/B	420	
	T	30	
	Y	Less than 2	
Pilot pressure (bar)	a/b	Less than 35	
	X	30	
Pilot pressure control range	For Hydraulic control	8.5 ~22.5 bar (123 ~ 330 psi)	
Required control $\Delta p$ at the control block	Compensator-T: 25bar (360psi) Compensator-S; C: 18bar (260psi)		
Recommended hydraulic pilot control units	See H-2TH6 characteristic curve 97		
LS pressure relief function (adjustment ranges)	50 ~ 149 bar; 150 ~ 330bar		

### Electric


Normal E-H operation	<ul style="list-style-type: none"> <li>·Electrical on/off valve: Installed on the 'A'side cover</li> <li>·Connection: Deutsch DT04-2P or AMP Junior-Timer</li> <li>·Protection class: IP69k</li> <li>·Supply voltage: 12 or 24VDC</li> </ul>	<ul style="list-style-type: none"> <li>·Electrical proportional valve: Installed on the 'A' side cover</li> <li>·Dither frequency required: 150Hz</li> <li>·Hysteresis: Less than 3%(at valid range)</li> <li>·Connection: Deutsch DT04-2P or AMP Junior-Timer</li> <li>·Protection class: IP69k</li> <li>·Reducing pressure range: 0~30 bar</li> <li>·Control current@24VDC: 0~800mA, @12VDC: 0~1500mA</li> </ul>
-------------------------	--	--




### Using environment

Hydraulic fluid	Mineral oil (HL, HLP) according to DIN 51524. Other hydraulic fluids, such as HEES (Synthetic Ester) according to VDMA 24568.
Hydraulic fluid temperature range( )	-20 to + 80
Viscosity range $\nu$ (mm <sup>2</sup> /s)	10 to 380
Maximum permissible degree of contamination of the pressure fluid cleanliness class to ISO 4406 (C)	Class 20/18/15, we therefore recommend a filter with a minimum retention rate of $\beta_{10} \geq 75$


(For applications outside above mentioned parameters, please consult our sales dept.)

### Ordering code



Basic code	① Structure	LSPV	Stackable, proportional control, load sensing, pressure compensated
	② Nominal size		15
	③ Number of blocks	..	01~09
Inlet element	④ Circuit types	J	Closed center, for variable piston pump system
		p	Open center, for fixed displacement pump system
	⑤ Main relief valve	Q	Without main pressure relief valve(not for open center)
Middle section	⑥ Spool function	S	With load-holding function, with pressure compensator
		T	Without load-holding function, with pressure compensator
		C	With load-holding function, without pressure compensator
	⑦ LS relief valve	QM...	Only with B port LS pressure relief valve, with LS measuring port (pressure in bar, 3-digits)
		...M...	With LS pressure relief valve, with LS measuring port (pressure in bar, 3-digits)
		...MQ	Only with A port LS pressure relief valve, with LS measuring port (pressure in bar, 3-digits)
		...R...	With remote LS pressure relief valve, decreasing characteristic curve, with LS measuring port (pressure in bar, 3-digits)
		...L...	With remote LS pressure relief valve, increasing characteristic curve, with LS measuring port (pressure in bar, 3-digits)
	⑧ Spool symbol	E	 =E
		J	 =J
Q		 =Q	
⑨ A/B flow	...—...	Flow in l/min, 3-digits, e.g. 50-50	


### Ordering code



Middle section	⑩ 'A' side cover	M0	Mechanical, standard spring centered (M1: Mechanical, friction detent)		
		H	Hydraulic		
		W21	E-H operation, proportional control, 24V		
		W23	E-H operation, proportional control, 12V		
		W41	E-H operation, on/off control, 24V		
		W43	E-H operation, on/off control, 12V		
		OBE	Super high performance E-H control		
	⑪ 'B' side cover	Blank	Standard cover		
		1(K/L)	Hand lever		
			Hand lever position		
K			L —**		
2	Without hand lever (can be added if any demand)				
⑫ A/B port relief valve	QQ	Plug, without relief valve (port relief valve can be added)			
	GG	Check valve, for anti-cavitation function			
	H...H...	H320H320, pressure in bar, pressure details of port relief valve in 3 digits			
End element	⑬ LS unload	LZ	Without LS unload function		
		LA	With LS unload function		
	⑭ Additional P port	Blank	Without additional P port		
		PT	With additional P port		
	⑮ Pilot pressure control	X	Internal pilot pressure supply		
		Y	External pilot pressure supply		
Others	⑯ Sealing type	V	FKM		
		N	NBR		
	⑰ Design code	001			
⑱ Special application	Blank	Without special requirement	-450	Without aluminum material	
*	Other request	Further requirement in the clear text			


### Ordering code

Basic code	LSPV 15		
1- Inlet element	P	Open center, for fixed displacement pump system	
	J	Closed center, for variable displacement pump system	
2- Middle section	'A' side cover	M0	Mechanical, standard spring centered
		M1	Mechanical, friction detent
		H	Hydraulic
		W21	E-H operation, proportional control, 24V
	'B' side cover	1K	Hand lever
		Blank	Standard cover
3- End element	LS unload	LZ	Without LS unload function
		LA	With LS unload function
	Pilot pressure control	X	Internal pilot pressure supply
		Y	External pilot pressure supply




Exploded view (example: LSPV15)

## Hydraulic Diagram



- |  |   |
|--|---|
| 1 Pump connection                                      | 10 Work port                              |
| 2 Load sensing port                                    | 11 Main pressure relief valve             |
| 3 Tank connection                                      | 12 Pressure compensator                   |
| 4.1 B side LS pressure measure port                    | 13 Spool                                  |
| 4.2 A side LS pressure measure port                    | 14 Plug                                   |
| 5 Load-signal connection for parallel- valve (plugged) | 15 Port pressure relief valve             |
| 6 No back pressure connection to tank                  | 16 Electrical proportional reducing valve |
| 7 External pilot oil supply                            | 17 LS pressure relief valve               |
| 8 Pump pressure measure port                           | 18.1 / 18.2 Shuttle valve                 |
| 9 Pilot port   | 19 Pressure reducing and relief valve     |


**Inlet section — closed center**



Port dimension		Thread dimensions		
P port:	G1	G1:	ΦD 47	L 19
T port:	G1	G1/4:	ΦD 24	L 12
LS port:	G1/4			





### Spool section assembly—hydraulic



• Spool stroke adjustable

□ Hydraulic operation H



**Port dimension**

A/B port: G3/4


Pilot port/Ma/Mb port: G1/4

**Thread dimensions**

G3/4:  $\Phi$ D 38 L 16


G1/4:  $\Phi$ D 24 L 12

### Spool section assembly—electro-hydraulic





•Spool stroke adjustable

E-H proportional control  
W21 24V; W23 12V









E-H on/off control  
W41 24V; W43 12V





Port dimension		Thread dimensions		
A/B port:	G3/4	G3/4:	ΦD 38	L 16
Ma/Mb port:	G1/4	G1/4:	ΦD 24	L 12

### Middle section—OBE (Super high performance E-H control)




Port dimension	Thread dimensions		
A/B port: G3/4	G3/4:	ΦD 38	L 16
Ma/Mb port: G1/4	G1/4:	ΦD 24	L 12

**Endlet section assembly (without additional P port)**



Port dimension		Thread dimensions		
Tt port:	G3/4	G3/4:	ΦD 38	L 16
Y port:	G1/4	G1/4:	ΦD 24	L 12
X port:	G1/4			
LSZ port:	G1/4			

**Endlet section assembly (with additional P port)**



Port dimension		Thread dimensions	
P1 port:	G3/4	G3/4:	ΦD 38 L 16
Tt Port:	G3/4	G1/4:	ΦD 24 L 12
Y Port:	G1/4		
X Port:	G1/4		
LSZ Port:	G1/4		

## Preferred spool flow

### Symmetry spool

Pressure compensator	Flow(L/min)						
S	160-160	150-150	120-120	080-080	050-050	032-032	023-023
	140-140	130-130	100-100	070-070	045-045	028-028	020-020
	120-120	110-110	085-085	060-060	040-040	025-025	017-017
C	200-200	175-175	145-145	110-110	080-080	045-045	028-028
T	200-200	190-190	160-160	100-100	065-065	040-040	

### Asymmetry spool

Pressure compensator	Flow(L/min)				
S	150-120	120-180	080-050	050-032	023-014
	130-110	100-070	070-045	045-028	020-012
	110-085	085-060	060-040	040-025	017-010
C	175-145	145-110	110-080	080-045	
T	190-160	160-100	100-065	065-040	028-017

Example:


\* Pressure compensator: S

\* Command flow value:  $Q_{ac} = 145$  L/min

Solution:


→ 110 L/min spool + 2 washers = 150 L/min

→ Set 145 L/min via stroke limitation




## Unit Dimensions

(Dimensions in mm)




### Pressure compensator type




#### Code 'S'

With pressure compensator  
With load holding function



#### Code 'T'


With pressure compensator  
Without load holding function



#### Code 'C'


Without pressure compensator  
With load holding function

### End elements option



#### End element with LS unloading

Ordering code: LA



#### End element without LS unloading

Ordering code: LZ  
Short description  
Supply of tandem switched LS signals

## On-board electronics: OBE

The internal closed loop position control configuration of the OBE control cover makes the valve spool achieve the desired position with accuracy levels approaching the performance of a servo-valve, by continuously comparing the set-point of a remote control device ( potentiometer, joystick , machine management system) with the feedback signal generated by a high precision hall effect position transducer.

### Choice between different types of control:

- 1 -Analog control (0 – 5V), with following auxiliary signals available:
  - spool position feedback
  - 5V for external potentiometer or joystick
- 2 - CANbus control (J1939 or CANopen protocols)




### SPOOL STROKE A

When the input voltage signal fed to the MLTFD5 actuator is maintained within 2.25 and 2.75V, the directional valve spool is at rest (Neutral Dead Band). When  $V_{in} = 2.75V$ , the spool steps up from NEUTRAL to MINIMUM FLOW control position. A linear ramp from MIN. to MAX. spool stroke will follow by increasing  $V_{in}$  from 2.75 to 4.1V. At  $V_{in} = 4.50V$ , the spool is brought into its FLOAT POSITION, if present. By decreasing the input voltage from 4.1 to 2.75V, the spool stroke is linearly reduced and after the oil flow is fully shut-off, a step-down from MINIMUM FLOW to NEUTRAL position takes place.

### SPOOL STROKE B

Same as for STROKE A, by varying  $V_{in}$  from 2.25 to 0.9V, the spool will go from NEUTRAL to MAX. STROKE in the opposite direction.

Spool Stroke (mm) VS Input Voltage Signal (Volt DC)



### ALARM / FAIL - SAFE MODE

An input voltage variation beyond the calibration range (<0.25V or >4.75V) will bring the system into an ALARM mode, urging the spool to return to its NEUTRAL position until  $V_{in}$  is brought back to its nominal control range.

## Technical data


### Hydraulic specifications:

Max. supply pressure: 35 bar  
 Min. supply pressure: 12bar  
 Max. back pressure: 1.5bar  
 Pilot flow requirement: 0.2 L/min  
 Filtration: 18/15(ISO 4406)

### Electrical specifications:

Operating voltage: 8-30VDC  
 Max,. current consumption: 750mA/s  
 Analog input impedance: >40kOhm  
 Analog input signal: 0-5 V  
 Protection class: IP68

## Connector pinout ( Front view)



### D/A0

1. + Power Supply
2. Do not Connect
3. Control Signal
4. - Power Supply (GND)

### D/A5

1. + Power Supply
2. + 5V Aux. Supply voltage
3. Control Signal
4. - Power Supply (GND)

### D/AF

1. + Power Supply
2. Sensor Feedback Output
3. Control Signal
4. - Power Supply (GND)

### D/C0

1. + Power Supply
2. CANL
3. CANH
4. - Power Supply (GND)

